

Tabela A-4 – Propriedades da água saturada (líquido e vapor), entrada de temperaturas

Temp. °C <i>T</i>	Sat. press. kPa <i>P<sub>sat</sub></i>	Specific volume m <sup>3</sup> /kg		Internal energy kJ/kg			Enthalpy kJ/kg			Entropy kJ/(kg · K)		
		Sat. liquid <i>v<sub>f</sub></i>	Sat. vapor <i>v<sub>g</sub></i>	Sat. liquid <i>u<sub>f</sub></i>	Evap. <i>u<sub>fg</sub></i>	Sat. vapor <i>u<sub>g</sub></i>	Sat. liquid <i>h<sub>f</sub></i>	Evap. <i>h<sub>fg</sub></i>	Sat. vapor <i>h<sub>g</sub></i>	Sat. liquid <i>s<sub>f</sub></i>	Evap. <i>s<sub>fg</sub></i>	Sat. vapor <i>s<sub>g</sub></i>
0.01	0.6113	0.001 000	206.14	0.0	2375.3	2375.3	0.01	2501.3	2501.4	0.000	9.1562	9.1562
5	0.8721	0.001 000	147.12	20.97	2361.3	2382.3	20.98	2489.6	2510.6	0.0761	8.9496	9.0257
10	1.2276	0.001 000	106.38	42.00	2347.2	2389.2	42.01	2477.7	2519.8	0.1510	8.7498	8.9008
15	1.7051	0.001 001	77.93	62.99	2333.1	2396.1	62.99	2465.9	2528.9	0.2245	8.5569	8.7814
20	2.339	0.001 002	57.79	83.95	2319.0	2402.9	83.96	2454.1	2538.1	0.2966	8.3706	8.6672
25	3.169	0.001 003	43.36	104.88	2304.9	2409.8	104.89	2442.3	2547.2	0.3674	8.1905	8.5580
30	4.246	0.001 004	32.89	125.78	2290.8	2416.6	125.79	2430.5	2556.3	0.4369	8.0164	8.4533
35	5.628	0.001 006	25.22	146.67	2276.7	2423.4	146.68	2418.6	2565.3	0.5053	7.8478	8.3531
40	7.384	0.001 008	19.52	167.56	2262.6	2430.1	167.57	2406.7	2574.3	0.5725	7.6845	8.2570
45	9.593	0.001 010	15.26	188.44	2248.4	2436.8	188.45	2394.8	2583.2	0.6387	7.5261	8.1648
50	12.349	0.001 012	12.03	209.32	2234.2	2443.5	209.33	2382.7	2592.1	0.7038	7.3725	8.0763
55	15.758	0.001 015	9.568	230.21	2219.9	2450.1	230.23	2370.7	2600.9	0.7679	7.2234	7.9913
60	19.940	0.001 017	7.671	251.11	2205.5	2456.6	251.13	2358.5	2609.6	0.8312	7.0784	7.9096
65	25.03	0.001 020	6.197	272.02	2191.1	2463.1	272.06	2346.2	2618.3	0.8935	6.9375	7.8310
70	31.19	0.001 023	5.042	292.95	2176.6	2469.6	292.98	2333.8	2626.8	0.9549	6.8004	7.7553
75	38.58	0.001 026	4.131	313.90	2162.0	2475.9	313.93	2321.4	2635.3	1.0155	6.6669	7.6824
80	47.39	0.001 029	3.407	334.86	2147.4	2482.2	334.91	2308.8	2643.7	1.0753	6.5369	7.6122
85	57.83	0.001 033	2.828	355.84	2132.6	2488.4	355.90	2296.0	2651.9	1.1343	6.4102	7.5445
90	70.14	0.001 036	2.361	376.85	2117.7	2494.5	376.92	2283.2	2660.1	1.1925	6.2866	7.4791
95	84.55	0.001 040	1.982	397.88	2102.7	2500.6	397.96	2270.2	2668.1	1.2500	6.1659	7.4159
<b>Sat. press. MPa</b>												
100	0.101 35	0.001 044	1.6729	418.94	2087.6	2506.5	419.04	2257.0	2676.1	1.3069	6.0480	7.3549
105	0.120 82	0.001 048	1.4194	440.02	2072.3	2512.4	440.15	2243.7	2683.8	1.3630	5.9328	7.2958
110	0.143 27	0.001 052	1.2102	461.14	2057.0	2518.1	461.30	2230.2	2691.5	1.4185	5.8202	7.2387
115	0.169 06	0.001 056	1.0366	482.30	2041.4	2523.7	482.48	2216.5	2699.0	1.4734	5.7100	7.1833
120	0.198 53	0.001 060	0.8919	503.50	2025.8	2529.3	503.71	2202.6	2706.3	1.5276	5.6020	7.1296
125	0.2321	0.001 065	0.7706	524.74	2009.9	2534.6	524.99	2188.5	2713.5	1.5813	5.4962	7.0775
130	0.2701	0.001 070	0.6685	546.02	1993.9	2539.9	546.31	2174.2	2720.5	1.6344	5.3925	7.0269
135	0.3130	0.001 075	0.5822	567.35	1977.7	2545.0	567.69	2159.6	2727.3	1.6870	5.2907	6.9777
140	0.3613	0.001 080	0.5089	588.74	1961.3	2550.0	589.13	2144.7	2733.9	1.7391	5.1908	6.9299
145	0.4154	0.001 085	0.4463	610.18	1944.7	2554.9	610.63	2129.6	2740.3	1.7907	5.0926	6.8833
150	0.4758	0.001 091	0.3928	631.68	1927.9	2559.5	632.20	2114.3	2746.5	1.8418	4.9960	6.8379
155	0.5431	0.001 096	0.3468	653.24	1910.8	2564.1	653.84	2098.6	2752.4	1.8925	4.9010	6.7935
160	0.6178	0.001 102	0.3071	674.87	1893.5	2568.4	675.55	2082.6	2758.1	1.9427	4.8075	6.7502
165	0.7005	0.001 108	0.2727	696.56	1876.0	2572.5	697.34	2066.2	2763.5	1.9925	4.7153	6.7078
170	0.7917	0.001 114	0.2428	718.33	1858.1	2576.5	719.21	2049.5	2768.7	2.0419	4.6244	6.6663
175	0.8920	0.001 121	0.2168	740.17	1840.0	2580.2	741.17	2032.4	2773.6	2.0909	4.5347	6.6256
180	1.0021	0.001 127	0.194 05	762.09	1821.6	2583.7	763.22	2015.0	2778.2	2.1396	4.4461	6.5857
185	1.1227	0.001 134	0.174 09	784.10	1802.9	2587.0	785.37	1997.1	2782.4	2.1879	4.3586	6.5465
190	1.2544	0.001 141	0.156 54	806.19	1783.8	2590.0	807.62	1978.8	2786.4	2.2359	4.2720	6.5079
195	1.3978	0.001 149	0.141 05	828.37	1764.4	2592.8	829.98	1960.0	2790.0	2.2835	4.1863	6.4698

**Tabela A-4 – Propriedades da água saturada (líquido e vapor), entrada de temperaturas (continuação)**

Temp. °C <i>T</i>	Sat. press. MPa <i>P<sub>sat</sub></i>	Specific volume m <sup>3</sup> /kg		Internal energy kJ/kg			Enthalpy kJ/kg			Entropy kJ/(kg · K)		
		Sat. liquid <i>v<sub>f</sub></i>	Sat. vapor <i>v<sub>g</sub></i>	Sat. liquid <i>u<sub>f</sub></i>	Evap. <i>u<sub>fg</sub></i>	Sat. vapor <i>u<sub>g</sub></i>	Sat. liquid <i>h<sub>f</sub></i>	Evap. <i>h<sub>fg</sub></i>	Sat. vapor <i>h<sub>g</sub></i>	Sat. liquid <i>s<sub>f</sub></i>	Evap. <i>s<sub>fg</sub></i>	Sat. vapor <i>s<sub>g</sub></i>
200	1.5538	0.001 157	0.127 36	850.65	1744.7	2595.3	852.45	1940.7	2793.2	2.3309	4.1014	6.4323
205	1.7230	0.001 164	0.115 21	873.04	1724.5	2597.5	875.04	1921.0	2796.0	2.3780	4.0172	6.3952
210	1.9062	0.001 173	0.104 41	895.53	1703.9	2599.5	897.76	1900.7	2798.5	2.4248	3.9337	6.3585
215	2.104	0.001 181	0.094 79	918.14	1682.9	2601.1	920.62	1879.9	2800.5	2.4714	3.8507	6.3221
220	2.318	0.001 190	0.086 19	940.87	1661.5	2602.4	943.62	1858.5	2802.1	2.5178	3.7683	6.2861
225	2.548	0.001 199	0.078 49	963.73	1639.6	2603.3	966.78	1836.5	2803.3	2.5639	3.6863	6.2503
230	2.795	0.001 209	0.071 58	986.74	1617.2	2603.9	990.12	1813.8	2804.0	2.6099	3.6047	6.2146
235	3.060	0.001 219	0.065 37	1009.89	1594.2	2604.1	1013.62	1790.5	2804.2	2.6558	3.5233	6.1791
240	3.344	0.001 229	0.059 76	1033.21	1570.8	2604.0	1037.32	1766.5	2803.8	2.7015	3.4422	6.1437
245	3.648	0.001 240	0.054 71	1056.71	1546.7	2603.4	1061.23	1741.7	2803.0	2.7472	3.3612	6.1083
250	3.973	0.001 251	0.050 13	1080.39	1522.0	2602.4	1085.36	1716.2	2801.5	2.7927	3.2802	6.0730
255	4.319	0.001 263	0.045 98	1104.28	1596.7	2600.9	1109.73	1689.8	2799.5	2.8383	3.1992	6.0375
260	4.688	0.001 276	0.042 21	1128.39	1470.6	2599.0	1134.37	1662.5	2796.9	2.8838	3.1181	6.0019
265	5.081	0.001 289	0.038 77	1152.74	1443.9	2596.6	1159.28	1634.4	2793.6	2.9294	3.0368	5.9662
270	5.499	0.001 302	0.035 64	1177.36	1416.3	2593.7	1184.51	1605.2	2789.7	2.9751	2.9551	5.9301
275	5.942	0.001 317	0.032 79	1202.25	1387.9	2590.2	1210.07	1574.9	2785.0	3.0208	2.8730	5.8938
280	6.412	0.001 332	0.030 17	1227.46	1358.7	2586.1	1235.99	1543.6	2779.6	3.0668	2.7903	5.8571
285	6.909	0.001 348	0.027 77	1253.00	1328.4	2581.4	1262.31	1511.0	2773.3	3.1130	2.7070	5.8199
290	7.436	0.001 366	0.025 57	1278.92	1297.1	2576.0	1289.07	1477.1	2766.2	3.1594	2.6227	5.7821
295	7.993	0.001 384	0.023 54	1305.2	1264.7	2569.9	1316.3	1441.8	2758.1	3.2062	2.5375	5.7437
300	8.581	0.001 404	0.021 67	1332.0	1231.0	2563.0	1344.0	1404.9	2749.0	3.2534	2.4511	5.7045
305	9.202	0.001 425	0.019 948	1359.3	1195.9	2555.2	1372.4	1366.4	2738.7	3.3010	2.3633	5.6643
310	9.856	0.001 447	0.018 350	1387.1	1159.4	2546.4	1401.3	1326.0	2727.3	3.3493	2.2737	5.6230
315	10.547	0.001 472	0.016 867	1415.5	1121.1	2536.6	1431.0	1283.5	2714.5	3.3982	2.1821	5.5804
320	11.274	0.001 499	0.015 488	1444.6	1080.9	2525.5	1461.5	1238.6	2700.1	3.4480	2.0882	5.5362
330	12.845	0.001 561	0.012 996	1505.3	993.7	2498.9	1525.3	1140.6	2665.9	3.5507	1.8909	5.4417
340	14.586	0.001 638	0.010 797	1570.3	894.3	2464.6	1594.2	1027.9	2622.0	3.6594	1.6763	5.3357
350	16.513	0.001 740	0.008 813	1641.9	776.6	2418.4	1670.6	893.4	2563.9	3.7777	1.4335	5.2112
360	18.651	0.001 893	0.006 945	1725.2	626.3	2351.5	1760.5	720.3	2481.0	3.9147	1.1379	5.0526
370	21.03	0.002 213	0.004 925	1844.0	384.5	2228.5	1890.5	441.6	2332.1	4.1106	0.6865	4.7971
374.14	22.09	0.003 155	0.003 155	2029.6	0	2029.6	2099.3	0	2099.3	4.4298	0	4.4298

Tabela A-5 - Propriedades da água saturada (líquido e vapor), entrada de pressões

Press. kPa <i>P</i>	Sat. temp. °C <i>T<sub>sat</sub></i>	Specific volume m <sup>3</sup> /kg		Internal energy kJ/kg			Enthalpy kJ/kg			Entropy kJ/(kg · K)		
		Sat. liquid <i>v<sub>f</sub></i>	Sat. vapor <i>v<sub>g</sub></i>	Sat. liquid <i>u<sub>f</sub></i>	Evap. <i>u<sub>fg</sub></i>	Sat. vapor <i>u<sub>g</sub></i>	Sat. liquid <i>h<sub>f</sub></i>	Evap. <i>h<sub>fg</sub></i>	Sat. vapor <i>h<sub>g</sub></i>	Sat. liquid <i>s<sub>f</sub></i>	Evap. <i>s<sub>fg</sub></i>	Sat. vapor <i>s<sub>g</sub></i>
0.6113	0.01	0.001 000	206.14	0.00	2375.3	2375.3	0.01	2501.3	2501.4	0.0000	9.1562	9.1562
1.0	6.98	0.001 000	129.21	29.30	2355.7	2385.0	29.30	2484.9	2514.2	0.1059	8.8697	8.9756
1.5	13.03	0.001 001	87.98	54.71	2338.6	2393.3	54.71	2470.6	2525.3	0.1957	8.6322	8.8279
2.0	17.50	0.001 001	67.00	73.48	2326.0	2399.5	73.48	2460.0	2533.5	0.2607	8.4629	8.7237
2.5	21.08	0.001 002	54.25	88.48	2315.9	2404.4	88.49	2451.6	2540.0	0.3120	8.3311	8.6432
3.0	24.08	0.001 003	45.67	101.04	2307.5	2408.5	101.05	2444.5	2545.5	0.3545	8.2231	8.5776
4.0	28.96	0.001 004	34.80	121.45	2293.7	2415.2	121.46	2432.9	2554.4	0.4226	8.0520	8.4746
5.0	32.88	0.001 005	28.19	137.81	2282.7	2420.5	137.82	2423.7	2561.5	0.4764	7.9187	8.3951
7.5	40.29	0.001 008	19.24	168.78	2261.7	2430.5	168.79	2406.0	2574.8	0.5764	7.6750	8.2515
10	45.81	0.001 010	14.67	191.82	2246.1	2437.9	191.83	2392.8	2584.7	0.6493	7.5009	8.1502
15	53.97	0.001 014	10.02	225.92	2222.8	2448.7	225.94	2373.1	2599.1	0.7549	7.2536	8.0085
20	60.06	0.001 017	7.649	251.38	2205.4	2456.7	251.40	2358.3	2609.7	0.8320	7.0766	7.9085
25	64.97	0.001 020	6.204	271.90	2191.2	2463.1	271.93	2346.3	2618.2	0.8931	6.9383	7.8314
30	69.10	0.001 022	5.229	289.20	2179.2	2468.4	289.23	2336.1	2625.3	0.9439	6.8247	7.7686
40	75.87	0.001 027	3.993	317.53	2159.5	2477.0	317.58	2319.2	2636.8	1.0259	6.6441	7.6700
50	81.33	0.001 030	3.240	340.44	2143.4	2483.9	340.49	2305.4	2645.9	1.0910	6.5029	7.5939
75	91.78	0.001 037	2.217	384.31	2112.4	2496.7	384.39	2278.6	2663.0	1.2130	6.2434	7.4564
<b>Press. MPa</b>												
0.100	99.63	0.001 043	1.6940	417.36	2088.7	2506.1	417.46	2258.0	2675.5	1.3026	6.0568	7.3594
0.125	105.99	0.001 048	1.3749	444.19	2069.3	2513.5	444.32	2241.0	2685.4	1.3740	5.9104	7.2844
0.150	111.37	0.001 053	1.1593	466.94	2052.7	2519.7	467.11	2226.5	2693.6	1.4336	5.7897	7.2233
0.175	116.06	0.001 057	1.0036	486.80	2038.1	2524.9	486.99	2213.6	2700.6	1.4849	5.6868	7.1717
0.200	120.23	0.001 061	0.8857	504.49	2025.0	2529.5	504.70	2201.9	2706.7	1.5301	5.5970	7.1271
0.225	124.00	0.001 064	0.7933	520.47	2013.1	2533.6	520.72	2191.3	2712.1	1.5706	5.5173	7.0878
0.250	127.44	0.001 067	0.7187	535.10	2002.1	2537.2	535.37	2181.5	2716.9	1.6072	5.4455	7.0527
0.275	130.60	0.001 070	0.6573	548.59	1991.9	2540.5	548.89	2172.4	2721.3	1.6408	5.3801	7.0209
0.300	133.55	0.001 073	0.6058	561.15	1982.4	2543.6	561.47	2163.8	2725.3	1.6718	5.3201	6.9919
0.325	136.30	0.001 076	0.5620	572.90	1973.5	2546.4	573.25	2155.8	2729.0	1.7006	5.2646	6.9652
0.350	138.88	0.001 079	0.5243	583.95	1965.0	2548.9	584.33	2148.1	2732.4	1.7275	5.2130	6.9405
0.375	141.32	0.001 081	0.4914	594.40	1956.9	2551.3	594.81	2140.8	2735.6	1.7528	5.1647	6.9175
0.40	143.63	0.001 084	0.4625	604.31	1949.3	2553.6	604.74	2133.8	2738.6	1.7766	5.1193	6.8959
0.45	147.93	0.001 088	0.4140	622.77	1934.9	2557.6	623.25	2120.7	2743.9	1.8207	5.0359	6.8565
0.50	151.86	0.001 093	0.3749	639.68	1921.6	2561.2	640.23	2108.5	2748.7	1.8607	4.9606	6.8213
0.55	155.48	0.001 097	0.3427	655.32	1909.2	2564.5	665.93	2097.0	2753.0	1.8973	4.8920	6.7893
0.60	158.85	0.001 101	0.3157	669.90	1897.5	2567.4	670.56	2086.3	2756.8	1.9312	4.8288	6.7600
0.65	162.01	0.001 104	0.2927	683.56	1886.5	2570.1	684.28	2076.0	2760.3	1.9627	4.7703	6.7331
0.70	164.97	0.001 108	0.2729	696.44	1876.1	2572.5	697.22	2066.3	2763.5	1.9922	4.7158	6.7080
0.75	167.78	0.001 112	0.2556	708.64	1866.1	2574.7	709.47	2057.0	2766.4	2.0200	4.6647	6.6847
0.80	170.43	0.001 115	0.2404	720.22	1856.6	2576.8	721.11	2048.0	2769.1	2.0462	4.6166	6.6628
0.85	172.96	0.001 118	0.2270	731.27	1847.4	2578.7	732.22	2039.4	2771.6	2.0710	4.5711	6.6421
0.90	175.38	0.001 121	0.2150	741.83	1838.6	2580.5	742.83	2031.1	2773.9	2.0946	4.5280	6.6226
0.95	177.69	0.001 124	0.2042	751.95	1830.2	2582.1	753.02	2023.1	2776.1	2.1172	4.4869	6.6041
1.00	179.91	0.001 127	0.19444	761.68	1822.0	2583.6	762.81	2015.3	2778.1	2.1387	4.4478	6.5865
1.10	184.09	0.001 133	0.17753	780.09	1806.3	2586.4	781.34	2000.4	2781.7	2.1792	4.3744	6.5536
1.20	187.99	0.001 139	0.16333	797.29	1791.5	2588.8	798.65	1986.2	2784.8	2.2166	4.3067	6.5233
1.30	191.64	0.001 144	0.15125	813.44	1777.5	2591.0	814.93	1972.7	2787.6	2.2515	4.2438	6.4953

Tabela A-5 - Propriedades da água saturada (líquido e vapor), entrada de pressões (continuação)

Press. MPa <i>P</i>	Sat. temp. °C <i>T<sub>sat</sub></i>	Specific volume m <sup>3</sup> /kg		Internal energy kJ/kg			Enthalpy kJ/kg			Entropy kJ/(kg · K)		
		Sat. liquid <i>v<sub>f</sub></i>	Sat. vapor <i>v<sub>g</sub></i>	Sat. liquid <i>u<sub>f</sub></i>	Evap. <i>u<sub>fg</sub></i>	Sat. vapor <i>u<sub>g</sub></i>	Sat. liquid <i>h<sub>f</sub></i>	Evap. <i>h<sub>fg</sub></i>	Sat. vapor <i>h<sub>g</sub></i>	Sat. liquid <i>s<sub>f</sub></i>	Evap. <i>s<sub>fg</sub></i>	Sat. vapor <i>s<sub>g</sub></i>
1.40	195.07	0.001 149	0.140 84	828.70	1764.1	2592.8	830.30	1959.7	2790.0	2.2842	4.1850	6.4693
1.50	198.32	0.001 154	0.131 77	843.16	1751.3	2594.5	844.89	1947.3	2792.2	2.3150	4.1298	6.4448
1.75	205.76	0.001 166	0.113 49	876.46	1721.4	2597.8	878.50	1917.9	2796.4	2.3851	4.0044	6.3896
2.00	212.42	0.001 177	0.099 63	906.44	1693.8	2600.3	908.79	1890.7	2799.5	2.4474	3.8935	6.3409
2.25	218.45	0.001 187	0.088 75	933.83	1668.2	2602.0	936.49	1865.2	2801.7	2.5035	3.7937	6.2972
2.5	223.99	0.001 197	0.079 98	959.11	1644.0	2603.1	962.11	1841.0	2803.1	2.5547	3.7028	6.2575
3.0	233.90	0.001 217	0.066 68	1004.78	1599.3	2604.1	1008.42	1795.7	2804.2	2.6457	3.5412	6.1869
3.5	242.60	0.001 235	0.057 07	1045.43	1558.3	2603.7	1049.75	1753.7	2803.4	2.7253	3.4000	6.1253
4	250.40	0.001 252	0.049 78	1082.31	1520.0	2602.3	1087.31	1714.1	2801.4	2.7964	3.2737	6.0701
5	263.99	0.001 286	0.039 44	1147.81	1449.3	2597.1	1154.23	1640.1	2794.3	2.9202	3.0532	5.9734
6	275.64	0.001 319	0.032 44	1205.44	1384.3	2589.7	1213.35	1571.0	2784.3	3.0267	2.8625	5.8892
7	285.88	0.001 351	0.027 37	1257.55	1323.0	2580.5	1267.00	1505.1	2772.1	3.1211	2.6922	5.8133
8	295.06	0.001 384	0.023 52	1305.57	1264.2	2569.8	1316.64	1441.3	2758.0	3.2068	2.5364	5.7432
9	303.40	0.001 418	0.020 48	1350.51	1207.3	2557.8	1363.26	1378.9	2742.1	3.2858	2.3915	5.6722
10	311.06	0.001 452	0.018 026	1393.04	1151.4	2544.4	1407.56	1317.1	2724.7	3.3596	2.2544	5.6141
11	318.15	0.001 489	0.015 987	1433.7	1096.0	2529.8	1450.1	1255.5	2705.6	3.4295	2.1233	5.5527
12	324.75	0.001 527	0.014 263	1473.0	1040.7	2513.7	1491.3	1193.3	2684.9	3.4962	1.9962	5.4924
13	330.93	0.001 567	0.012 780	1511.1	985.0	2496.1	1531.5	1130.7	2662.2	3.5606	1.8718	5.4323
14	336.75	0.001 611	0.011 485	1548.6	928.2	2476.8	1571.1	1066.5	2637.6	3.6232	1.7485	5.3717
15	342.24	0.001 658	0.010 337	1585.6	869.8	2455.5	1610.5	1000.0	2610.5	3.6848	1.6249	5.3098
16	347.44	0.001 711	0.009 306	1622.7	809.0	2431.7	1650.1	930.6	2580.6	3.7461	1.4994	5.2455
17	352.37	0.001 770	0.008 364	1660.2	744.8	2405.0	1690.3	856.9	2547.2	3.8079	1.3698	5.1777
18	357.06	0.001 840	0.007 489	1698.9	675.4	2374.3	1732.0	777.1	2509.1	3.8715	1.2329	5.1044
19	361.54	0.001 924	0.006 657	1739.9	598.1	2338.1	1776.5	688.0	2464.5	3.9388	1.0839	5.0228
20	365.81	0.002 036	0.005 834	1785.6	507.5	2293.0	1826.3	583.4	2409.7	4.0139	0.9130	4.9269
21	369.89	0.002 207	0.004 952	1842.1	388.5	2230.6	1888.4	446.2	2334.6	4.1075	0.6938	4.8013
22	373.80	0.002 742	0.003 568	1961.9	125.2	2087.1	2022.2	143.4	2165.6	4.3110	0.2216	4.5327
22.09	374.14	0.003 155	0.003 155	2029.6	0	2029.6	2099.3	0	2099.3	4.4298	0	4.4298

Tabela A-6 – Propriedades do vapor sobreaquecido

$T$ °C	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/(kg · K)	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/(kg · K)	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/(kg · K)
<b><math>P = 0.01 \text{ MPa (45.81°C)*}</math></b>				<b><math>P = 0.05 \text{ MPa (81.33°C)}</math></b>				<b><math>P = 0.10 \text{ MPa (99.63°C)}</math></b>				
Sat.†	14.674	2437.9	2584.7	8.1502	3.240	2483.9	2645.9	7.5939	1.6940	2506.1	2675.5	7.3594
50	14.869	2443.9	2592.6	8.1749								
100	17.196	2515.5	2687.5	8.4479	3.418	2511.6	2682.5	7.6947	1.6958	2506.7	2676.2	7.3614
150	19.512	2587.9	2783.0	8.6882	3.889	2585.6	2780.1	7.9401	1.9364	2582.8	2776.4	7.6134
200	21.825	2661.3	2879.5	8.9038	4.356	2659.9	2877.7	8.1580	2.172	2658.1	2875.3	7.8343
250	24.136	2736.0	2977.3	9.1002	4.820	2735.0	2976.0	8.3556	2.406	2733.7	2974.3	8.0333
300	26.445	2812.1	3076.5	9.2813	5.284	2811.3	3075.5	8.5373	2.639	2810.4	3074.3	8.2158
400	31.063	2968.9	3279.6	9.6077	6.209	2968.5	3278.9	8.8642	3.103	2967.9	3278.2	8.5435
500	35.679	3132.3	3489.1	9.8978	7.134	3132.0	3488.7	9.1546	3.565	3131.6	3488.1	8.8342
600	40.295	3302.5	3705.4	10.1608	8.057	3302.2	3705.1	9.4178	4.028	3301.9	3704.4	9.0976
700	44.911	3479.6	3928.7	10.4028	8.981	3479.4	3928.5	9.6599	4.490	3479.2	3928.2	9.3398
800	49.526	3663.8	4159.0	10.6281	9.904	3663.6	4158.9	9.8852	4.952	3663.5	4158.6	9.5652
900	54.141	3855.0	4396.4	10.8396	10.828	3854.9	4396.3	10.0967	5.414	3854.8	4396.1	9.7767
1000	58.757	4053.0	4640.6	11.0393	11.751	4052.9	4640.5	10.2964	5.875	4052.8	4640.3	9.9764
1100	63.372	4257.5	4891.2	11.2287	12.674	4257.4	4891.1	10.4859	6.337	4257.3	4891.0	10.1659
1200	67.987	4467.9	5147.8	11.4091	13.597	4467.8	5147.7	10.6662	6.799	4467.7	5147.6	10.3463
1300	72.602	4683.7	5409.7	11.5811	14.521	4683.6	5409.6	10.8382	7.260	4683.5	5409.5	10.5183
<b><math>P = 0.20 \text{ MPa (120.23°C)}</math></b>				<b><math>P = 0.30 \text{ MPa (133.55°C)}</math></b>				<b><math>P = 0.40 \text{ MPa (143.63°C)}</math></b>				
Sat.	0.8857	2529.5	2706.7	7.1272	0.6058	2543.6	2725.3	6.9919	0.4625	2553.6	2738.6	6.8959
150	0.9596	2576.9	2768.8	7.2795	0.6339	2570.8	2761.0	7.0778	0.4708	2564.5	2752.8	6.9299
200	1.0803	2654.4	2870.5	7.5066	0.7163	2650.7	2865.6	7.3115	0.5342	2646.8	2860.5	7.1706
250	1.1988	2731.2	2971.0	7.7086	0.7964	2728.7	2967.6	7.5166	0.5951	2726.1	2964.2	7.3789
300	1.3162	2808.6	3071.8	7.8926	0.8753	2806.7	3069.3	7.7022	0.6548	2804.8	3066.8	7.5662
400	1.5493	2966.7	3276.6	8.2218	1.0315	2965.6	3275.0	8.0330	0.7726	2964.4	3273.4	7.8985
500	1.7814	3130.8	3487.1	8.5133	1.1867	3130.0	3486.0	8.3251	0.8893	3129.2	3484.9	8.1913
600	2.013	3301.4	3704.0	8.7770	1.3414	3300.8	3703.2	8.5892	1.0055	3300.2	3702.4	8.4558
700	2.244	3478.8	3927.6	9.0194	1.4957	3478.4	3927.1	8.8319	1.1215	3477.9	3926.5	8.6987
800	2.475	3663.1	4158.2	9.2449	1.6499	3662.9	4157.8	9.0576	1.2372	3662.4	4157.3	8.9244
900	2.705	3854.5	4395.8	9.4566	1.8041	3854.2	4395.4	9.2692	1.3529	3853.9	4395.1	9.1362
1000	2.937	4052.5	4640.0	9.6563	1.9581	4052.3	4639.7	9.4690	1.4685	4052.0	4639.4	9.3360
1100	3.168	4257.0	4890.7	9.8458	2.1121	4256.8	4890.4	9.6585	1.5840	4256.5	4890.2	9.5256
1200	3.399	4467.5	5147.5	10.0262	2.2661	4467.2	5147.1	9.8389	1.6996	4467.0	5146.8	9.7060
1300	3.630	4683.2	5409.3	10.1982	2.4201	4683.0	5409.0	10.0110	1.8151	4682.8	5408.8	9.8780
<b><math>P = 0.50 \text{ MPa (151.86°C)}</math></b>				<b><math>P = 0.60 \text{ MPa (158.85°C)}</math></b>				<b><math>P = 0.80 \text{ MPa (170.43°C)}</math></b>				
Sat.	0.3749	2561.2	2748.7	6.8213	0.3157	2567.4	2756.8	6.7600	0.2404	2576.8	2769.1	6.6628
200	0.4249	2642.9	2855.4	7.0592	0.3520	2638.9	2850.1	6.9665	0.2608	2630.6	2839.3	6.8158
250	0.4744	2723.5	2960.7	7.2709	0.3938	2720.9	2957.2	7.1816	0.2931	2715.5	2950.0	7.0384
300	0.5226	2802.9	3064.2	7.4599	0.4344	2801.0	3061.6	7.3724	0.3241	2797.2	3056.5	7.2328
350	0.5701	2882.6	3167.7	7.6329	0.4742	2881.2	3165.7	7.5464	0.3544	2878.2	3161.7	7.4089
400	0.6173	2963.2	3271.9	7.7938	0.5137	2962.1	3270.3	7.7079	0.3843	2959.7	3267.1	7.5716
500	0.7109	3128.4	3483.9	8.0873	0.5920	3127.6	3482.8	8.0021	0.4433	3126.0	3480.6	7.8673
600	0.8041	3299.6	3701.7	7.3522	0.6697	3299.1	3700.9	8.2674	0.5018	3297.9	3699.4	8.1333
700	0.8969	3477.5	3925.9	8.5952	0.7472	3477.0	3925.3	8.5107	0.5601	3476.2	3924.2	8.3770
800	0.9896	3662.1	4156.9	8.8211	0.8245	3661.8	4156.5	8.7367	0.6181	3661.1	4155.6	8.6033
900	1.0822	3853.6	4394.7	9.0329	0.9017	3853.4	4394.4	8.9486	0.6761	3852.8	4393.7	8.8153
1000	1.1747	4051.8	4639.1	9.2328	0.9788	4051.5	4638.8	9.1485	0.7340	4051.0	4638.2	9.0153
1100	1.2672	4256.3	4889.9	9.4224	1.0559	4256.1	4889.6	9.3381	0.7919	4255.6	4889.1	9.2050
1200	1.3596	4466.8	5146.6	9.6029	1.1330	4466.5	5146.3	9.5185	0.8497	4466.1	5145.9	9.3855
1300	1.4521	4682.5	5408.6	9.7749	1.2101	4682.3	5408.3	9.6906	0.9076	4681.8	5407.9	9.5575

\* A temperatura em parênteses é a temperatura de saturação à referida pressão.

† Propriedades do vapor saturado à referida pressão.



Tabela A-6 – Propriedades do vapor sobreaquecido (continuação)

$T$ °C	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/(kg · K)	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/(kg · K)	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/(kg · K)
<b><math>P = 4.0 \text{ MPa (250.40}^\circ\text{C)}</math></b>				<b><math>P = 4.5 \text{ MPa (257.49}^\circ\text{C)}</math></b>				<b><math>P = 5.0 \text{ MPa (263.99}^\circ\text{C)}</math></b>				
Sat.	0.049 78	2602.3	2801.4	6.0701	0.044 06	2600.1	2798.3	6.0198	0.039 44	2597.1	2794.3	5.9734
275	0.054 57	2667.9	2886.2	6.2285	0.047 30	2650.3	2863.2	6.1401	0.041 41	2631.3	2838.3	6.0544
300	0.058 84	2725.3	2960.7	6.3615	0.051 35	2712.0	2943.1	6.2828	0.045 32	2698.0	2924.5	6.2084
350	0.066 45	2826.7	3092.5	6.5821	0.058 40	2817.8	3080.6	6.5131	0.051 94	2808.7	3068.4	6.4493
400	0.073 41	2919.9	3213.6	6.7690	0.064 75	2913.3	3204.7	6.7047	0.057 81	2906.6	3195.7	6.6459
450	0.080 02	3010.2	3330.3	6.9363	0.070 74	3005.0	3323.3	6.8746	0.063 30	2999.7	3316.2	6.8186
500	0.086 43	3099.5	3445.3	7.0901	0.076 51	3095.3	3439.6	7.0301	0.068 57	3091.0	3433.8	6.9759
600	0.098 85	3279.1	3674.4	7.3688	0.087 65	3276.0	3670.5	7.3110	0.078 69	3273.0	3666.5	7.2589
700	0.110 95	3462.1	3905.9	7.6198	0.098 47	3459.9	3903.0	7.5631	0.088 49	3457.6	3900.1	7.5122
800	0.122 87	3650.0	4141.5	7.8502	0.109 11	3648.3	4139.3	7.7942	0.098 11	3646.6	4137.1	7.7440
900	0.134 69	3843.6	4382.3	8.0647	0.119 65	3842.2	4380.6	8.0091	0.107 62	3840.7	4378.8	7.9593
1000	0.146 45	4042.9	4628.7	8.2662	0.130 13	4041.6	4627.2	8.2108	0.117 07	4040.4	4625.7	8.1612
1100	0.158 17	4248.0	4880.6	8.4567	0.140 56	4246.8	4879.3	8.4015	0.126 48	4245.6	4878.0	8.3520
1200	0.169 87	4458.6	5138.1	8.6376	0.150 98	4457.5	5136.9	8.5825	0.135 87	4456.3	5135.7	8.5331
1300	0.181 56	4674.3	5400.5	8.8100	0.161 39	4673.1	5399.4	8.7549	0.145 26	4672.0	5398.2	8.7055
<b><math>P = 6.0 \text{ MPa (275.64}^\circ\text{C)}</math></b>				<b><math>P = 7.0 \text{ MPa (285.88}^\circ\text{C)}</math></b>				<b><math>P = 8.0 \text{ MPa (295.06}^\circ\text{C)}</math></b>				
Sat.	0.032 44	2589.7	2784.3	5.8892	0.027 37	2580.5	2772.1	5.8133	0.023 52	2569.8	2758.0	5.7432
300	0.036 16	2667.2	2884.2	6.0674	0.029 47	2632.2	2838.4	5.9305	0.024 26	2590.9	2785.0	5.7906
350	0.042 23	2789.6	3043.0	6.3335	0.035 24	2769.4	3016.0	6.2283	0.029 95	2747.7	2987.3	6.1301
400	0.047 39	2892.9	3177.2	6.5408	0.039 93	2878.6	3158.1	6.4478	0.034 32	2863.8	3138.3	6.3634
450	0.052 14	2988.9	3301.8	6.7193	0.044 16	2978.0	3287.1	6.6327	0.038 17	2966.7	3272.0	6.5551
500	0.056 65	3082.2	3422.2	6.8803	0.048 14	3073.4	3410.3	6.7975	0.041 75	3064.3	3398.3	6.7240
550	0.061 01	3174.6	3540.6	7.0288	0.051 95	3167.2	3530.9	6.9486	0.045 16	3159.8	3521.0	6.8778
600	0.065 25	3266.9	3658.4	7.1677	0.055 65	3260.7	3650.3	7.0894	0.048 45	3254.4	3642.0	7.0206
700	0.073 52	3453.1	3894.2	7.4234	0.062 83	3448.5	3888.3	7.3476	0.054 81	3443.9	3882.4	7.2812
800	0.081 60	3643.1	4132.7	7.6566	0.069 81	3639.5	4128.2	7.5822	0.060 97	3636.0	4123.8	7.5173
900	0.089 58	3837.8	4375.3	7.8727	0.076 69	3835.0	4371.8	7.7991	0.067 02	3832.1	4368.3	7.7351
1000	0.097 49	4037.8	4622.7	8.0751	0.083 50	4035.3	4619.8	8.0020	0.073 01	4032.8	4616.9	7.9384
1100	0.105 36	4243.3	4875.4	8.2661	0.090 27	4240.9	4872.8	8.1933	0.078 96	4238.6	4870.3	8.1300
1200	0.113 21	4454.0	5133.3	8.4474	0.097 03	4451.7	5130.9	8.3747	0.084 89	4449.5	5128.5	8.3115
1300	0.121 06	4669.6	5396.0	8.6199	0.103 77	4667.3	5393.7	8.5475	0.090 80	4665.0	5391.5	8.4842
<b><math>P = 9.0 \text{ MPa (303.40}^\circ\text{C)}</math></b>				<b><math>P = 10.0 \text{ MPa (311.06}^\circ\text{C)}</math></b>				<b><math>P = 12.5 \text{ MPa (327.89}^\circ\text{C)}</math></b>				
Sat.	0.020 48	2557.8	2742.1	5.6772	0.018 026	2544.4	2724.7	5.6141	0.013 495	2505.1	2673.8	5.4624
325	0.023 27	2646.6	2856.0	5.8712	0.019 861	2610.4	2809.1	5.7568				
350	0.025 80	2724.4	2956.6	6.0361	0.022 42	2699.2	2923.4	5.9443	0.016 126	2624.6	2826.2	5.7118
400	0.029 93	2848.4	3117.8	6.2854	0.026 41	2832.4	3096.5	6.2120	0.020 00	2789.3	3039.3	6.0417
450	0.033 50	2955.2	3256.6	6.4844	0.029 75	2943.4	3240.9	6.4190	0.022 99	2912.5	3199.8	6.2719
500	0.036 77	3055.2	3386.1	6.6576	0.032 79	3045.8	3373.7	6.5966	0.025 60	3021.7	3341.8	6.4618
550	0.039 87	3152.2	3511.0	6.8142	0.035 64	3144.6	3500.9	6.7561	0.028 01	3125.0	3475.2	6.6290
600	0.042 85	3248.1	3633.7	6.9589	0.038 37	3241.7	3625.3	6.9029	0.030 29	3225.4	3604.0	6.7810
650	0.045 74	3343.6	3755.3	7.0943	0.041 01	3338.2	3748.2	7.0398	0.032 48	3324.4	3730.4	6.9218
700	0.048 57	3439.3	3876.5	7.2221	0.043 58	3434.7	3870.5	7.1687	0.034 60	3422.9	3855.3	7.0536
800	0.054 09	3632.5	4119.3	7.4596	0.048 59	3628.9	4114.8	7.4077	0.038 69	3620.0	4103.6	7.2965
900	0.059 50	3829.2	4364.8	7.6783	0.053 49	3826.3	4361.2	7.6272	0.042 67	3819.1	4352.5	7.5182
1000	0.064 85	4030.3	4614.0	7.8821	0.058 32	4027.8	4611.0	7.8315	0.046 58	4021.6	4603.8	7.7237
1100	0.070 16	4236.3	4867.7	8.0740	0.063 12	4234.0	4865.1	8.0237	0.050 45	4228.2	4858.8	7.9165
1200	0.075 44	4447.2	5126.2	8.2556	0.067 89	4444.9	5123.8	8.2055	0.054 30	4439.3	5118.0	8.0937
1300	0.080 72	4662.7	5389.2	8.4284	0.072 65	4460.5	5387.0	8.3783	0.058 13	4654.8	5381.4	8.2717

Tabela A-6 – Propriedades do vapor sobreaquecido (continuação)

$T$ °C	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/(kg · K)	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/(kg · K)	$v$ m <sup>3</sup> /kg	$u$ kJ/kg	$h$ kJ/kg	$s$ kJ/(kg · K)
<b><math>P = 15.0 \text{ MPa (342.24}^\circ\text{C)}</math></b>				<b><math>P = 17.5 \text{ MPa (354.75}^\circ\text{C)}</math></b>				<b><math>P = 20.0 \text{ MPa (365.81}^\circ\text{C)}</math></b>				
Sat.	0.010 337	2455.5	2610.5	5.3098	0.007 920	2390.2	2528.8	5.1419	0.005 834	2293.0	2409.7	4.9269
350	0.011 470	2520.4	2692.4	5.4421					0.009 942	2619.3	2818.1	5.5540
400	0.015 649	2740.7	2975.5	5.8811	0.012 447	2685.0	2902.9	5.7213	0.012 695	2806.2	3060.1	5.9017
450	0.018 445	2879.5	3156.2	6.1404	0.015 174	2844.2	3109.7	6.0184	0.014 768	2942.9	3238.2	6.1401
500	0.020 80	2996.6	3308.6	6.3443	0.017 358	2970.3	3274.1	6.2383	0.016 555	3062.4	3393.5	6.3348
550	0.022 93	3104.7	3448.6	6.5199	0.019 288	3083.9	3421.4	6.4230	0.018 178	3174.0	3537.6	6.5048
600	0.024 91	3208.6	3582.3	6.6776	0.021 06	3191.5	3560.1	6.5866	0.019 693	3281.4	3675.3	6.6582
650	0.026 80	3310.3	3712.3	6.8224	0.022 74	3296.0	3693.9	6.7357	0.021 13	3386.4	3809.0	6.7993
700	0.028 61	3410.9	3840.1	6.9572	0.024 34	3398.7	3824.6	6.8736	0.023 85	3592.7	4069.7	7.0544
800	0.032 10	3610.9	4092.4	7.2040	0.027 38	3601.8	4081.1	7.1244	0.026 45	3797.5	4326.4	7.2830
900	0.035 46	3811.9	4343.8	7.4279	0.030 31	3804.7	4335.1	7.3507	0.028 97	4003.1	4582.5	7.4925
1000	0.038 75	4015.4	4596.6	7.6348	0.033 16	4009.3	4589.5	7.5589	0.031 45	4211.3	4840.2	7.6874
1100	0.042 00	4222.6	4852.6	7.8283	0.035 97	4216.9	4846.4	7.7531	0.033 91	4422.8	5101.0	7.8707
1200	0.045 23	4433.8	5112.3	8.0108	0.038 76	4428.3	5106.6	7.9360	0.036 36	4638.0	5365.1	8.0442
1300	0.048 45	4649.1	5376.0	8.1840	0.041 54	4643.5	5370.5	8.1093				
<b><math>P = 25.0 \text{ MPa}</math></b>				<b><math>P = 30.0 \text{ MPa}</math></b>				<b><math>P = 35.0 \text{ MPa}</math></b>				
375	0.001 973 1	1798.7	1848.0	4.0320	0.001 789 2	1737.8	1791.5	3.9305	0.001 700 3	1702.9	1762.4	3.8722
400	0.006 004	2430.1	2580.2	5.1418	0.002 790	2067.4	2151.1	4.4728	0.002 100	1914.1	1987.6	4.2126
425	0.007 881	2609.2	2806.3	5.4723	0.005 303	2455.1	2614.2	5.1504	0.003 428	2253.4	2373.4	4.7747
450	0.009 162	2720.7	2949.7	5.6744	0.006 735	2619.3	2821.4	5.4424	0.004 961	2498.7	2672.4	5.1962
500	0.011 123	2884.3	3162.4	5.9592	0.008 678	2820.7	3081.1	5.7905	0.006 927	2751.9	2994.4	5.6282
550	0.012 724	3017.5	3335.6	6.1765	0.010 168	2970.3	3275.4	6.0342	0.008 345	2921.0	3213.0	5.9026
600	0.014 137	3137.9	3491.4	6.3602	0.011 446	3100.5	3443.9	6.2331	0.009 527	3062.0	3395.5	6.1179
650	0.015 433	3251.6	3637.4	6.5229	0.012 596	3221.0	3598.9	6.4058	0.010 575	3189.8	3559.9	6.3010
700	0.016 646	3361.3	3777.5	6.6707	0.013 661	3335.8	3745.6	6.5606	0.011 533	3309.8	3713.5	6.4631
800	0.018 912	3574.3	4047.1	6.9345	0.015 623	3555.5	4024.2	6.8332	0.013 278	3536.7	4001.5	6.7450
900	0.021 045	3783.0	4309.1	7.1680	0.017 448	3768.5	4291.9	7.0718	0.014 883	3754.0	4274.9	6.9386
1000	0.023 10	3990.9	4568.5	7.3802	0.019 196	3978.8	4554.7	7.2867	0.016 410	3966.7	4541.1	7.2064
1100	0.025 12	4200.2	4828.2	7.5765	0.020 903	4189.2	4816.3	7.4845	0.017 895	4178.3	4804.6	7.4037
1200	0.027 11	4412.0	5089.9	7.7605	0.022 589	4401.3	5079.0	7.6692	0.019 360	4390.7	5068.3	7.5910
1300	0.029 10	4626.9	5354.4	7.9342	0.024 266	4616.0	5344.0	7.8432	0.020 815	4605.1	5333.6	7.7653
<b><math>P = 40.0 \text{ MPa}</math></b>				<b><math>P = 50.0 \text{ MPa}</math></b>				<b><math>P = 60.0 \text{ MPa}</math></b>				
375	0.001 640 7	1677.1	1742.8	3.8290	0.001 559 4	1638.6	1716.6	3.7639	0.001 502 8	1609.4	1699.5	3.7141
400	0.001 907 7	1854.6	1930.9	4.1135	0.001 730 9	1788.1	1874.6	4.0031	0.001 633 5	1745.4	1843.4	3.9318
425	0.002 532	2096.9	2198.1	4.5029	0.002 007	1959.7	2060.0	4.2734	0.001 816 5	1892.7	2001.7	4.1626
450	0.003 693	2365.1	2512.8	4.9459	0.002 486	2159.6	2284.0	4.5884	0.002 085	2053.9	2179.0	4.4121
500	0.005 622	2678.4	2903.3	5.4700	0.003 892	2525.5	2720.1	5.1726	0.002 956	2390.6	2567.9	4.9321
550	0.006 984	2869.7	3149.1	5.7785	0.005 118	2763.6	3019.5	5.5485	0.003 956	2658.8	2896.2	5.3441
600	0.008 094	3022.6	3346.4	6.0144	0.006 112	2942.0	3247.6	5.8178	0.004 834	2861.1	3151.2	5.6452
650	0.009 063	3158.0	3520.6	6.2054	0.006 966	3093.5	3441.8	6.0342	0.005 595	3028.8	3364.5	5.8829
700	0.009 941	3283.6	3681.2	6.3750	0.007 727	3230.5	3616.8	6.2189	0.006 272	3177.2	3553.5	6.0824
800	0.011 523	3517.8	3978.7	6.6662	0.009 076	3479.8	3933.6	6.5290	0.007 459	3441.5	3889.1	6.4109
900	0.012 962	3739.4	4257.9	6.9150	0.010 283	3710.3	4224.4	6.7882	0.008 508	3681.0	4191.5	6.6805
1000	0.014 324	3954.6	4527.6	7.1356	0.011 411	3930.5	4501.1	7.0146	0.009 480	3906.4	4475.2	6.9127
1100	0.015 642	4167.4	4793.1	7.3364	0.012 496	4145.7	4770.5	7.2184	0.010 409	4124.1	4748.6	7.1195
1200	0.016 940	4380.1	5057.7	7.5224	0.013 561	4359.1	5037.2	7.4058	0.011 317	4338.2	5017.2	7.3083
1300	0.018 229	4594.3	5323.5	7.6969	0.014 616	4572.8	5303.6	7.5808	0.012 215	4551.4	5284.3	7.4837

Tabela A-7 - Propriedades do líquido comprimido ou subarrefecido

<i>T</i> °C	<i>v</i> m <sup>3</sup> /kg	<i>u</i> kJ/kg	<i>h</i> kJ/kg	<i>s</i> kJ/(kg · K)	<i>v</i> m <sup>3</sup> /kg	<i>u</i> kJ/kg	<i>h</i> kJ/kg	<i>s</i> kJ/(kg · K)	<i>v</i> m <sup>3</sup> /kg	<i>u</i> kJ/kg	<i>h</i> kJ/kg	<i>s</i> kJ/(kg · K)
<b><i>P</i> = 5 MPa (263.99°C)</b>				<b><i>P</i> = 10 MPa (311.06°C)</b>				<b><i>P</i> = 15 MPa (342.24°C)</b>				
Sat.	0.001 285 9	1147.8	1154.2	2.9202	0.001 452 4	1393.0	1407.6	3.3596	0.001 658 1	1585.6	1610.5	3.6848
0	0.000 997 7	0.04	5.04	0.0001	0.000 995 2	0.09	10.04	0.0002	0.000 992 8	0.15	15.05	0.0004
20	0.000 999 5	83.65	88.65	0.2956	0.000 997 2	83.36	93.33	0.2945	0.000 995 0	83.06	97.99	0.2934
40	0.001 005 6	166.95	171.97	0.5705	0.001 003 4	166.35	176.38	0.5686	0.001 001 3	165.76	180.78	0.5666
60	0.001 014 9	250.23	255.30	0.8285	0.001 012 7	249.36	259.49	0.8258	0.001 010 5	248.51	263.67	0.8232
80	0.001 026 8	333.72	338.85	1.0720	0.001 024 5	332.59	342.83	1.0688	0.001 022 2	331.48	346.81	1.0656
100	0.001 041 0	417.52	422.72	1.3030	0.001 038 5	416.12	426.50	1.2992	0.001 036 1	414.74	430.28	1.2955
120	0.001 057 6	501.80	507.09	1.5233	0.001 054 9	500.08	510.64	1.5189	0.001 052 2	498.40	514.19	1.5145
140	0.001 076 8	586.76	592.15	1.7343	0.001 073 7	584.68	595.42	1.7292	0.001 070 7	582.66	598.72	1.7242
160	0.001 098 8	672.62	678.12	1.9375	0.001 095 3	670.13	681.08	1.9317	0.001 091 8	667.71	684.09	1.9260
180	0.001 124 0	759.63	765.25	2.1341	0.001 119 9	756.65	767.84	2.1275	0.001 115 9	753.76	770.50	2.1210
200	0.001 153 0	848.1	853.9	2.3255	0.001 148 0	844.5	856.0	2.3178	0.001 143 3	841.0	858.2	2.3104
220	0.001 186 6	938.4	944.4	2.5128	0.001 180 5	934.1	945.9	2.5039	0.001 174 8	929.9	947.5	2.4953
240	0.001 226 4	1031.4	1037.5	2.6979	0.001 218 7	1026.0	1038.1	2.6872	0.001 211 4	1020.8	1039.0	2.6771
260	0.001 274 9	1127.9	1134.3	2.8830	0.001 264 5	1121.1	1133.7	2.8699	0.001 255 0	1114.6	1133.4	2.8576
280					0.001 321 6	1220.9	1234.1	3.0548	0.001 308 4	1212.5	1232.1	3.0393
300					0.001 397 2	1328.4	1342.3	3.2469	0.001 377 0	1316.6	1337.3	3.2260
320									0.001 472 4	1431.1	1453.2	3.4247
340									0.001 631 1	1567.5	1591.9	3.6546
<b><i>P</i> = 20 MPa (365.81°C)</b>				<b><i>P</i> = 30 MPa</b>				<b><i>P</i> = 50 MPa</b>				
Sat.	0.002 036	1785.6	1826.3	4.0139	0.000 985 6	0.25	29.82	0.0001	0.000 976 6	0.20	49.03	0.0014
0	0.000 990 4	0.19	20.01	0.0004	0.000 988 6	82.17	111.84	0.2899	0.000 980 4	81.00	130.02	0.2848
20	0.000 992 8	82.77	102.62	0.2923	0.000 988 6	82.17	111.84	0.2899	0.000 987 2	161.86	211.21	0.5527
40	0.000 999 2	165.17	185.16	0.5646	0.000 995 1	164.04	193.89	0.5607	0.000 987 2	161.86	211.21	0.5527
60	0.001 008 4	247.68	267.85	0.8206	0.001 004 2	246.06	276.19	0.8154	0.000 996 2	242.98	292.79	0.8052
80	0.001 019 9	330.40	350.80	1.0624	0.001 015 6	328.30	358.77	1.0561	0.001 007 3	324.34	374.70	1.0440
100	0.001 033 7	413.39	434.06	1.2917	0.001 029 0	410.78	441.66	1.2844	0.001 020 1	405.88	456.89	1.2703
120	0.001 049 6	496.76	517.76	1.5102	0.001 044 5	493.59	524.93	1.5018	0.001 034 8	487.65	539.39	1.4857
140	0.001 067 8	580.69	602.04	1.7193	0.001 062 1	576.88	608.75	1.7098	0.001 051 5	569.77	622.35	1.6915
160	0.001 088 5	665.35	687.12	1.9204	0.001 082 1	660.82	693.28	1.9096	0.001 070 3	652.41	705.92	1.8891
180	0.001 112 0	750.95	773.20	2.1147	0.001 104 7	745.59	778.73	2.1024	0.001 091 2	735.69	790.25	2.0794
200	0.001 138 8	837.7	860.5	2.3031	0.001 130 2	831.4	865.3	2.2893	0.001 114 6	819.7	875.5	2.2634
220	0.001 169 5	925.9	949.3	2.4870	0.001 159 0	918.3	953.1	2.4711	0.001 140 8	904.7	961.7	2.4419
240	0.001 204 6	1016.0	1040.0	2.6674	0.001 192 0	1006.9	1042.6	2.6490	0.001 170 2	990.7	1049.2	2.6158
260	0.001 246 2	1108.6	1133.5	2.8459	0.001 230 3	1097.4	1134.3	2.8243	0.001 203 4	1078.1	1138.2	2.7860
280	0.001 296 5	1204.7	1230.6	3.0248	0.001 275 5	1190.7	1229.0	2.9986	0.001 241 5	1167.2	1229.3	2.9537
300	0.001 359 6	1306.1	1333.3	3.2071	0.001 330 4	1287.9	1327.8	3.1741	0.001 286 0	1258.7	1323.0	3.1200
320	0.001 443 7	1415.7	1444.6	3.3979	0.001 399 7	1390.7	1432.7	3.3539	0.001 338 8	1353.3	1420.2	3.2868
340	0.001 568 4	1539.7	1571.0	3.6075	0.001 492 0	1501.7	1546.5	3.5426	0.001 403 2	1452.0	1522.1	3.4557
360	0.001 822 6	1702.8	1739.3	3.8772	0.001 626 5	1626.6	1675.4	3.7494	0.001 483 8	1556.0	1630.2	3.6291
380					0.001 869 1	1781.4	1837.5	4.0012	0.001 588 4	1667.2	1746.6	3.8101